



EU - Type Examination Certificate

- Equipment and protective systems intended for use in potentially explosive atmospheres Directive 2014/34/EU (2)
- (3)EU - Type Examination Certificate Number

EPS 19 ATEX 1 077

Revision 0

(4)Equipment:

(1)

Actuator Type: ExRun-....-..

(5)Manufacturer: Schischek GmbH

Address:

Mühlsteig 45, Gewerbegebiet Süd 5

90579 Langenzenn

Germany

- This equipment and any acceptable variation thereto are specified in the annex to this certificate and the (7)documentation therein referred to.
- (8)Bureau Veritas Consumer Products Services Germany GmbH, notified body No. 2004 in accordance with Article 21 given in the Directive 2014/34/EU of the European Parliament and of the Council of 26 February 2014, certifies that this equipment has been found to comply with the essential health and safety requirements relating to the design and construction of equipment and protective systems intended for use in potentially explosive atmospheres, given in Annex II of the Directive. The examination and test results are recorded in the confidential documentation under the reference number 19TH0209.
- Compliance with the essential health and safety requirements has been assured by compliance with: (9)

EN 60079-0:2018

EN 60079-1:2014

EN 60079-7:2015+A1:2018

EN 60079-0:2012.A11:2013

EN 60079-31:2014

EN 60079-11:2012

- If the sign "X" is placed after the certificate number, it indicates that the equipment is subject to special conditions for safe use specified in the annex to this certificate.
- This EU Type Examination Certificate relates only to the design and examination of the specified equipment in (11)accordance with Directive 2014/34/EU. Further requirements of this Directive apply to the manufacture of this equipment and its placing on the market. Those requirements are not covered by this certificate.
- The marking of the equipment shall include the following:

II 2(2)G Ex db eb [ib Gb] IIC T6, T5, T4 Gb

tt 2(2)D Ex tb [ib Db] IIIC T80°C, T95°C, T130°C Db

Certification department of explosion protection

Schaffer

Hamburg, 2019-06-06

Page 1 of 3

Certificates without signature and seal are void. This certificate is allowed to be distributed only if not modified. Extracts or modifications must be authorized by Bureau Veritas Consumer Products Services Germany GmbH. EPS 19 ATEX 1 077, Revision 0.





(13) Annex

(14) EU - Type Examination Certificate EPS 19 ATEX 1 077

Revision 0

(15) Description of equipment:

The actuator, type ExRun-*** consists of a flameproof enclosure with actuator shafts that accommodate electromechanical components. The internal portion is temperature controlled. The flameproof enclosure is mounted in a protective housing together with additional mechanical components. The gears and mechanical actuators mounted in the protective housing do not form part of this type approval.

Connection is by means of a increased safety junction box

Electrical data:

Power supply: terminals 1-5 (X1, X	A)	
Nominal voltage U _o /U	up to	24 – 240 V
Rated voltage	max.	240 V
Rated current	max.	2,5 A
Option –S terminals 1-6 (XB)		
Nominal voltage U _o /U	up to	24- 230 V
Rated voltage	max.	240 V
Rated current	max.	5,0 A
Option –Y terminals 1-6 (X2, XB)		
Nominal voltage U _o /U	up to	24 V
Rated voltage	max.	24 V
Rated current		30 mA

Rated values are maximum values, the actual electrical values are determined by mounted electrical apparatus. Within these limiting values complying with the appropriate standards, the manufacturer specifies the final limiting values dependent on power supply specifications, operating mode, utilization category, etc. Any additional technical features are specified in the test documents and the operating manual.

Ambient temperature	Т6	-40 °C up to +40 °C
·	T5	-40 °C up to +50 °C
	T⊿	-40 °C up to +60 °C

Page 2 of 3





Intrinsic safe circuits

RS232, terminals 1-6 (EEXi output, SV101)	18.	
U _o		
lo		
Po		
Linear circuit		
Li negligible		
Ci negligible		

Maximum of external lumped capacitance and inductance:

	Ex ib		
	IIC	IIB	IIA
Lo	2 mH	2 mH	2 mH
Со	43 µF	1000 μF	1000 µF

5,88 V 119 mA 0,7 W

- (16) Reference number: 19TH0209
- (17) Special conditions for safe use:

None

(18) Essential health and safety requirements:

Met by compliance with standards.



Hamburg, 2019-06-06

Page 3 of 3