






Ex-d auxilliary switch, adaptable to ExMax actuators size S and M
 2 potential free contacts, adjustable on site.

Type	Technical data	Installation area
ExSwitch	Explosion proof, auxilliary switch with 2 adjustable contacts, potential free, adaptable to all ExMax-actuators size S and M	Zone 1, 2, 21, 22

Views

ExSwitch	Dimension in mm	View inside	Wiring diagram	Adaptation to actuator
				

Description

ExSwitch are adaptable auxilliary switches for use in hazardous areas for end and interim position indication.
 ExSwitch have 2 potential free contacts installed in a housing which can be fitted directly to ExMax actuators size S and M. Both contacts are adjustable. Adjustment during operation is possible.
 ExSwitch are delivered with a cable of approx. 1 m. For electrical connection inside hazardous areas, a special Ex-e terminal box is required (see accessories ExBox).

Explosion proof







ATEX	PTB 00 ATEX 1093 X, RL 94/9/EC (ATEX) IBExU 01 ATEX 1007 X
Use in zone 1 and 2	II2G Ex d IIC T6 for gas, mists and vapours
Use in zone 21 and 22	II2D Ex tD A21 IP66 T80°C for dust
IP-protection	IP66 in acc. with EN 60529

Mounting and adjustment

- Put the mechanical linkage into the squared connection of the actuator
- Mount the ExSwitch to the actuator and fix it with the screws
- Wire the actuator (Ex-e terminal box required!)
- Open the ExSwitch and adjust each switch with the adjustment bow. You have to open the screw to turn the cam switch, afterwards tighten the screw.
- Make a mechanical check that the switches are working in the required position.
- Lock the enclosure.

Technical data

Type	ExSwitch ExMax S+M
Adaptable to actuator	type ExMax -.. size S and M
Function	2 explosion proof auxilliary switches, potential free contact
Max. current AC/DC	24 VAC/DC, 3 A 240 VAC, 0,5 A
Mechanical life	2 × 10 ⁶ switch cycles
Cable connection	1 cable for each switch, approx. 1 m cable length, 3 × 0,75 mm ² , cable diameter ~ Ø 7,2 mm
Ambient temperature	-40...+40°C
Accuracy	< 5°
Switch hysteresis	< 5 %
Housing material	Steel, painted
Material Switch	Plastic, Thermoplast
Switch material	Changeover contact silver, gold plated, thermoplast for switches
Delivery	1 housing with 2 integral Ex d switches, incl. mechanical linkage to ExMax actuators size S or M, 4 screws, 1 adjustment bow, position indicator

ExMax Side L 0° - 5° HS2 on	ExMax Side R 0° - 5° HS1 on
	
ExMax Side L 85° - 90° HS1 on	ExMax Side R 85° - 90° HS2 on
	
	

Accessories (optional)

ExBox-...	Terminal box Ex-e
ExSwitch-...-CT	Housing in marine painting, outer parts in stainless steel